

Package ‘minimaxALT’

May 8, 2026

Type Package

Title Generate Optimal Designs of Accelerated Life Test using
PSO-Based Algorithm

Version 1.0.3

Encoding UTF-8

License GPL (>= 3)

Description A computationally efficient solution for generating optimal experimental designs in Accelerated Life Testing (ALT). Leveraging a Particle Swarm Optimization (PSO)-based hybrid algorithm, the package identifies optimal test plans that minimize estimation variance under specified failure models and stress profiles. For more detailed, see Lee et al. (2025), Optimal Robust Strategies for Accelerated Life Tests and Fatigue Testing of Polymer Composite Materials <doi:10.1214/25-AOAS2075>, and Hoang (2025), Model-Robust Minimax Design of Accelerated Life Tests via PSO-based Hybrid Algorithm, Master' Thesis, Unpublished.

SystemRequirements GNU Scientific Library (GSL), OpenMP

Imports Rcpp (>= 1.0.11), RcppArmadillo (>= 14.0.0.1), RcppGSL (>= 0.3.13), ggplot2 (>= 3.0.0), parallel (>= 4.0.0), stats, graphics

Depends R (>= 4.0.0)

LinkingTo Rcpp (>= 1.0.11), RcppArmadillo (>= 14.0.0.1), RcppGSL (>= 0.3.13)

RoxygenNote 7.3.2

URL <https://github.com/hoanglinh171/minimaxALT>

BugReports <https://github.com/hoanglinh171/minimaxALT/issues>

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation yes

Author Hoai-Linh Hoang [aut, cre],
I-Chen Lee [aut],
Ping-Yang Chen [aut],
Ray-Bing Chen [aut],
Weng Kee Wong [aut]

Maintainer Hoai-Linh Hoang <hoailinh.hoang17@gmail.com>

Repository CRAN

Date/Publication 2025-12-23 08:00:02 UTC

Contents

check_equivalence_theorem	2
find_optimal_alt	3
initialize_values	5
pso_setting	6
set_design_info	8
Index	9

check_equivalence_theorem
Check Equivalence Theorem for Optimal Design

Description

Evaluates whether a design satisfies the equivalence theorem.

Usage

```
check_equivalence_theorem(best_design, model_set, design_info, seed = 42)
```

Arguments

best_design	A matrix containing stress levels and allocated proportion of the design.
model_set	A matrix of models, including parameters and distribution, that maximize the optimality criteria with the given best particle's position.
design_info	A list containing design parameters such as factor levels, number of units, and other settings.
seed	Seed for reproducibility

Value

max_directional_derivative Maximum directional derivative within design space.

model_set The model set that is input.

model_weight The weight assigned to each model in the model set.

equivalence_data Generated designs and their corresponding directional derivative given the optimal design best_particle. Each design is a combination of factors with value in [0, 1]. These designs are data for plotting equivalence theorem plot.

References

1. Müller, C. H., & Pázman, A. (1998). Applications of necessary and sufficient conditions for maximin efficient designs. *Metrika*, 48, 1–19.
2. Huang, M.-N. L., & Lin, C.-S. (2006). Minimax and maximin efficient designs for estimating the location-shift parameter of parallel models with dual responses. *Journal of Multivariate Analysis*, 97(1), 198–210.

Examples

```
design_info <- set_design_info(k_levels=2, j_factor=1, n_unit=300,
                             censor_time=183, p=0.1, use_cond=0, sigma=0.6)

best_design <- rbind(
  c(0.682, 1),
  c(0.706, 0.294)
)

model_set <- rbind(
  c(0.01, 0.9, 1),
  c(0.01, 0.99, 2))

equi <- check_equivalence_theorem (best_design=best_design,
                                   model_set=model_set,
                                   design_info=design_info)

equi$max_directional_derivative
```

find_optimal_alt

Find Optimal ALT Design Using Hybrid Algorithm

Description

Runs hybrid algorithm combining PSO and Nelder-Mead to find the optimal design of accelerated life test (ALT).

Usage

```
find_optimal_alt(
  design_type,
  distribution,
  design_info,
  pso_info,
  coef = NULL,
  coef_lower = NULL,
  coef_upper = NULL,
  init_values = NULL,
  highest_level = TRUE,
```

```

n_threads = 1,
verbose = TRUE,
seed = 42
)

```

Arguments

<code>design_type</code>	Integer. 1: Locally optimal design, 2: Minimax design.
<code>distribution</code>	Integer. The assumed failure time distribution, 1: Weibull, 2: Log-normal, 3: Model robust (both distribution Weibull and Log-normal).
<code>design_info</code>	A list from 'set_design_info()' containing design specifications.
<code>pso_info</code>	A list from 'pso_setting()' defining PSO hyperparameters.
<code>coef</code>	Optional. Fixed model coefficients. Required if <code>design_type = 1</code> .
<code>coef_lower</code>	Optional. Lower bounds for model parameters. Required if <code>design_type = 2</code> .
<code>coef_upper</code>	Optional. Upper bounds for model parameters. Required if <code>design_type = 2</code> .
<code>init_values</code>	Optional. A list of initial values from 'initialize_values()'.
<code>highest_level</code>	Logical. Whether the highest stress level of the generated design is the upper bound of stress range <code>x_h</code> . Default value is TRUE.
<code>n_threads</code>	Integer. Number of threads for parallel processing.
<code>verbose</code>	Logical. If TRUE, print optimization progress.
<code>seed</code>	Integer. Seed for reproducibility

Value

g_best	The global best design found by the hybrid algorithm.
coef_best	The parameters corresponding to the global best design.
distribution_best	The distribution corresponding to the global best design.
max_directional_derivative	Maximum directional derivative within design space, evaluated using equivalence theorem.
fg_best	The objective function value corresponding to the global best design.
fg_best_hist	A vector tracking the best objective function value of each iteration.
p_best	A matrix containing each particle's personal best design found during the optimization.
fp_best	A vector containing the objective function values corresponding to each particle's personal best.
g_hist	All particle positions of each iteration.
coef_best_hist	The parameters corresponding to the global best designs of each iteration.
distribution_best_hist	The distribution corresponding to the global best designs of each iteration.
model_set	A matrix containing distribution and model parameters of global best particles of each iteration, duplicated models are removed.
model_weight	The weight assigned to each model in the model set.
equivalence_data	Generated designs and their corresponding directional derivative given the optimal design <code>g_best</code> . Each design is a combination of factors with value in $[0, 1]$. These designs are data for plotting equivalence theorem plot.

References

1. Chen P (2024). `_globpso`: Particle Swarm Optimization Algorithms and Differential Evolution for Minimization Problems_. R package version 1.2.1, <<https://github.com/PingYangChen/globpso>>.
2. Kennedy, J., & Eberhart, R. (1995). Particle swarm optimization. In Proceedings of the IEEE International Conference on Neural Networks (ICNN) (Vol. 4, pp. 1942–1948).
3. Lee, I. C., Chen, R. B., Wong, W. K., (in press). Optimal Robust Strategies for Accelerated Life Tests and Fatigue Testing of Polymer Composite Materials. *Annals of Applied Statistics*. <<https://imstat.org/journals-and-publications/annals-of-applied-statistics/annals-of-applied-statistics-next-issues/>>
4. Meeker, W. Q., & Escobar, L. A. (1998). *Statistical methods for reliability data*. New York: Wiley-Interscience.
5. Nelder, J. A. and Mead, R. (1965). A simplex algorithm for function minimization. *Computer Journal*, 7, 308–313. 10.1093/comjnl/7.4.308.

Examples

```
design_info <- set_design_info(k_levels=2, j_factor=1, n_unit=300,
                             censor_time=183, p=0.1, use_cond=0, sigma=0.6)

pso_info <- pso_setting(n_swarm=32, max_iter=128, early_stopping=10, tol=0.01)

set.seed(42)
res <- find_optimal_alt(design_type=1, distribution=1, design_info=design_info,
                      pso_info=pso_info, coef=c(0.001, 0.9), verbose = FALSE)

summary(res)
plot(res, x_l=0, x_h=1)
```

initialize_values	<i>Initialize Particle Swarm Optimization and Nelder-Mead Algorithm Values</i>
-------------------	--------------------------------------------------------------------------------

Description

Sets initial particles for PSO, initial locally optimal design, and initial parameters for Nelder-Mead algorithm.

Usage

```
initialize_values(init_swarm = NULL, init_local = NULL, init_coef_mat = NULL)
```

Arguments

- `init_swarm` Optional matrix of initial particle positions. If not defined, particle positions are randomly generated using `runif` with pre-determined number of particles `n_swarm` and particle size.
- `init_local` Optional vector of initial locally optimal design. If not defined, the initial vector representing locally optimal design is `c(1, 0.6, 0.3)`.
- `init_coef_mat` Optional matrix of initial parameters to implement multi-start Nelder-Mead algorithm. The number of rows is the number of starts, and each row is the corresponding initial parameters. If not defined, the initial matrix of parameters is generated by sigmoid transformation of `10 * as.matrix(expand.grid(rep(list(c(1, -1)), j_factor + 1)))`.

Value

A list of initialized values.

Examples

```
init_local <- c(1, 0.6, 0.3)

init_coef_mat <- rbind(
  c(1e-6, 0.99),
  c(1e-2, 1),
  c(1.01e-6, 0.9999))

j_factor <- 1
k_levels <- 3
n_swarm <- 32
d_swarm <- (j_factor + 1) * k_levels - 1
init_swarm <- matrix(runif(n_swarm*d_swarm), nrow=n_swarm, byrow=TRUE)

init_values <- initialize_values(init_swarm=init_swarm,
                                init_local=init_local,
                                init_coef_mat=init_coef_mat)
```

pso_setting

Set PSO Optimization Settings

Description

Define hyperparameters for particle swarm optimization (PSO).

Usage

```
pso_setting(  
  n_swarm = 32,  
  max_iter = 128,  
  early_stopping = 10,  
  tol = 0.01,  
  c1 = 2.05,  
  c2 = 2.05,  
  w0 = 1.2,  
  w1 = 0.2,  
  w_var = 0.8,  
  vk = 4  
)
```

Arguments

n_swarm	Integer. Number of particles in the swarm.
max_iter	Integer. Maximum number of iterations.
early_stopping	Integer. The frequency, i.e. number of iterations, of validating the design optimality using equivalence theorem. The optimization process stops once maximum directional derivative is approximately 1.
tol	Numeric. Convergence tolerance. The algorithm stops if $\text{abs}(\text{max_directional_derivative} - 1) < \text{tol}$.
c1	Numeric. Cognitive acceleration coefficient. Default value is 2.05.
c2	Numeric. Social acceleration coefficient. Default value is 2.05.
w0	Numeric. Starting inertia weight. Default value is 1.2.
w1	Numeric. Ending inertia weight. Default value is 0.2.
w_var	Numeric. A number between $[0, 1]$ that controls the percentage of iterations during which PSO linearly decrease inertia weight from w_0 to w_1 . Default value is 0.8.
vk	Numeric. Velocity clamping factor. Default value is 4.

Value

A list of PSO hyperparameters.

Examples

```
pso_info <- pso_setting(n_swarm=32, max_iter=128, early_stopping=10, tol=0.01)
```

set_design_info	<i>Set ALT Design Information</i>
-----------------	-----------------------------------

Description

Configures the settings for an accelerated life test.

Usage

```
set_design_info(
  k_levels,
  j_factor,
  n_unit,
  censor_time,
  p,
  use_cond,
  sigma,
  x_l = 0,
  x_h = 1,
  reparam = TRUE
)
```

Arguments

k_levels	Integer. Number of stress levels.
j_factor	Integer. Number of stress factors.
n_unit	Integer. Total number of test units.
censor_time	Numeric. Test duration or censoring time.
p	Numeric. $0 < p < 1$. Lifetime percentile to be estimated at the use condition, i.e. stress levels are 0.
use_cond	Vector. Stress levels at the use condition.
sigma	Numeric. Scale parameter of the lifetime distribution.
x_l	Numeric. Lower bound of stress range. Default is 0.
x_h	Numeric. Upper bound of stress range. Default is 1.
reparam	Logical. Whether reparameterization is applied to model parameters. Reparameterization is supported for all design types, while non-reparameterization is only available for locally optimal design <code>design_type = 1</code> . Default is TRUE.

Value

A list of design specifications

Examples

```
design_info <- set_design_info(k_levels=3, j_factor=1, n_unit=300,
                             censor_time=183, p=0.1, use_cond=c(0), sigma=0.6)
```

Index

`check_equivalence_theorem`, [2](#)

`find_optimal_alt`, [3](#)

`initialize_values`, [5](#)

`pso_setting`, [6](#)

`set_design_info`, [8](#)